

Value Proposition

Technical know-how and a lubricant recommendation from Dow Corning applications engineers helped drive costs down.

Application

Lubrication of vacuum pump in chemicals processing plant.

Problem

High-purity synthetic oil was rapidly oxidizing, resulting in a buildup of tar and varnish that caused pump seizure every four to seven days.

Solution

New technology ultra high-purity synthetic blend vacuum pump oil.

Product Selected

Molykote® Brand L-1668FG vacuum pump oil

Results

Eliminated buildup of tar and varnish, increasing maintenance intervals 15-fold and saving over \$12,000 in related costs during the first year of operation.

DRIVE COSTS DOWN

Vacuum Pump Lubrication

Molykote® brand Synthetic Blend Oil Eliminates Tar Buildup, Seizing in Vacuum Pump

Lubrication technicians helped a chemicals manufacturer drive costs down by solving a vacuum pump failure, increasing the pump's maintenance intervals 15-fold and saving over \$12,000 in related costs during the first year of operation.

Dow Corning had been using a high-purity synthetic oil in a vacuum pump at one of the processing plants in its chemical manufacturing complex in Auburn, Michigan. The oil, however, was causing a buildup of tar and varnish that resulted in pump seizure every four to seven days.

The problem involved two rotary vane pumps operating in alternating 24-hour shifts, which powered vacuum wands used to transport materials inside a clean room environment. They were located side-by-side and supported a continuous 24/7 materials handling application. The application requires that the pumps provide 1X10⁻⁴ Torr, so they operate at very hot temperatures, well in excess of 60°C (140°F).

"The oil would last from four to seven days, then the pumps would fail," says Rod Vesterfelt, shop team leader. "During switch over at start-up, the corresponding pump would actually be seized up. We typically found that the oil inside had become a sticky, tar-like substance. We think this was the cause of the seizure, and it was probably due to the oil's poor performance in high operating temperatures," he explains.

Rebuilding and cleaning the pumps required two to three hours of work, but unplanned breakdowns during the continuous process operation often required calling in maintenance staff during off hours. "It put pressure on our maintenance budget and it sometimes brought our production lines to a halt."

Synthetic Blend Lasts Longer

Vesterfelt and his staff decided to consider replacing the synthetic oil with a new synthetic blend oil. They chose **Molykote®** Brand L-1668FG Synthetic Blend Vacuum Pump Oil from Dow Corning—a blend of polyalphaolefin (PAO) and ultra high-purity mineral oil—which they set up for a head-to-head test with the oil that had been failing. The **Molykote®** oil was placed in one of the pumps, while the other was left operating with the competitive oil. The competitive oil continued to gum up at intervals of four to seven days, while the pump lubricated with **Molykote®** operated flawlessly for 60 days, or about a 15-fold increase in continuous operating time over the competition.

"The **Molykote®** oil was discolored somewhat, but oil analysis showed that it retained its viscosity. We were so pleased by its performance that we replaced the oil in the companion pump, too, and have had virtually no problems since then. In fact, we were so pleased that we decided to put **Molykote®** in all our vacuum pumps—about 50 altogether."



DOW CORNING

AV05748

“Based on an average of one hour of maintenance for each pump per month, we estimate the switch saves us about \$12,000 per year, and it virtually eliminates losses due to down time associated with lubricant breakdown.”

Molykote® Oils Resist Premature Breakdown

Dow Corning explains that the reason why **Molykote®** Brand Oil L-1668FG provides better performance in vacuum pump applications is because **Molykote®** lubricating oils are produced differently from other oils. Competitive oils are often produced by lower-quality methods—such as a solvent-based refining process rather than hydro cracking—and are fortified with inferior additive technology than what can be found in **Molykote®** oils. In addition, compared to lesser-quality base stocks and additive technology, **Molykote®** oils provide better protection and resistance to oxidation and other factors that contribute to premature oil breakdown.

Furthermore, while many competitive multi-purpose oils are sometimes recommended for vacuum pumps, they can contain additives that are not appropriate for some applications. Some additives that are needed in hydraulic or gear oils, for example, are not required in vacuum pump or compressor oils and can actually shorten their service life under certain operating conditions. This is particularly true for vacuum pumps and compressors, which typically have high operating temperatures and are exposed to process gasses, increased oxygen concentration, and humidity—conditions that facilitate chemical reactions between the operating environment and formulated lubricating oils.

The result is shortened oil lifetime and maintenance intervals due to additive depletion, oil oxidation, sludge and varnish formation and/or, under the right conditions, acid formation. As oil degrades, the by-products of its breakdown cause varnish build-up on the internal metal surface between the tips of the rotary vanes and the inside casing of the pumps. This development reduces lubricity and generates wear-related heat while creating an uneven surface that results in vacuum loss.

Chemical Engineering Is Key To Success

Molykote® brand synthetic and hydrocarbon-based oils, by comparison, are made by chemically building complex molecules from hydrocarbon building blocks that feature identical, strong molecular bonds in a saturated molecular structure. This structure produces ultra high purity base oils that provide increased resistance to oxygen attack and reduced heat-generated friction. These superior base stocks are then fortified with the correct high-quality, technically advanced additives that are matched to the applications for which the oil is intended. The resulting oils are more resistant to oxidation and adverse chemical reactions, which helps extend service intervals and the lifetime of the equipment they were designed to protect.

The improved performance of **Molykote®** synthetic lubricants contributed to increased vacuum pump efficiencies and resulted in several benefits. They helped reduce friction and component wear by achieving proper lubrication at start-up more quickly than conventional oils. Since less energy was lost to friction, costs were reduced due to lower power consumption. Finally, the reduced friction resulted in lower operating temperatures so the vacuum pump operated cooler, which enabled the lubricant to last longer than its rated lifetime.

During the 60 days after switching to **Molykote®** Brand L-1668FG Synthetic Blend Vacuum Pump Oil, the pump operated flawlessly and without the tar and varnish buildup that was causing pump failure.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Dow Corning's products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that the product will meet the Dow Corning sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Dow Corning and Molykote are registered trademarks of Dow Corning Corporation.

We help you invent the future. is a trademark of Dow Corning Corporation.

©2003 Dow Corning Corporation. All rights reserved.

Printed in USA

FPH33750-Europe

Form No.80-3181a-01

DOW CORNING

*We help you
invent the future.™*

www.dowcorning.com